## WR 6251

## 产品简介

名称: 聚羧酸减水剂大单体 产品类型: 聚醚大单体

产品说明及特性: 本品主要作为生产高性能聚羧酸减水剂的大单体,采用国际先进的烷氧基化装置、PRESS 五代技术生产,产品分子量准确、外观洁白,分子量分布较窄,二醇含量低,除具有WR 6251 的全部优良性能外,合成聚羧酸减水剂的减水率和保坍性能更好,具有更高性价比,是一款综合减水、保坍型产品,可应用在现场搅拌及远距离输送的高性能、高强度(C60以上)的商品混凝土中。

## 技术指标

项目/单位	典型值	测试标准
外观 (25℃)	白色至浅黄色片状	-
水分 %(m/m)	≤0.5	GB/T 6283-2008
pH (1% 水溶液 )	5.0-7.0	GB/T 6368-2008
羟值 (mg KOH/g)	16-20	GB/T 7383-2007
不饱和度 mmol/g	≥0.265	GB/T 12008.6-2010
双键保留率(%)	≥90	-

## 产品包装及贮运要求

本产品采用 25kg 编织袋包装;

产品无毒,不易燃,按一般化学品贮存和运输;

贮存于干燥通风处,避免阳光直射和雨淋,贮运温度不宜高于40℃,保质期1年。

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

服务电话: 4000-456-986 www.levima.cn